



8W Interchangeable Plug Series PSM08R Adapter with Micro-USB connector Meets EISA and CEC Requirements



Features

- Double Insulated
- Field Changeable AC Plugs
- Efficiency Level V Compliance
- 5% NL-FL Regulation
- Low Leakage Current
- Micro-USB Connector
- Class B EMI

Applications

- Wireless Communications
- Networking
- Portable Equipment
- Peripherals

Safety Approvals

- cUL/UL
- TUV
- SAA
- CCC
- CE
- C-Tick
- PSE

Mechanical Characteristics

- Length: 71.7mm (2.82in)
- Width: 45mm (1.77in)
- Height: 29.79mm (1.17in)
- Weight: 128g (4.52oz)

Output Specifications

Model	DC Output Voltage	Load		Ripple (1) P-P (max)	Regulation		Efficiency Level
		Min.	Max.		Line	Load	
PSM08R-050(M)	5V	0A	1.6A	100mV	±5%		IV

Note: (1) Measured with by-pass capacitors 0.1uf/10uf at output connector terminal and oscilloscope set at 20 mHz. (Tested by oscilloscope after waiting 1 minute)

Phihong is not responsible for any error and change. Content is subject to change without notice. Please consult the factory and visit www.phihong.com for the most up-to-date specifications.

INPUT:

AC Input Voltage Rating

100 to 240VAC

AC Input Voltage Range

90 to 264VAC

AC Input Frequency

47 to 63 Hz

AC Input Current

0.3A(RMS) max. @ 120VAC

0.15A(RMS) max. @ 240VAC

Leakage Current

250uA max. @ 264VAC

Inrush Current (cold)

40-60A for 120VAC at max. load (varies in voltage)

(Cold start @ ambient 25°C)

Input Power Saving

0.3W max. @ 240VAC

OUTPUT:

Efficiency

69% min. using Energystar method

Hold-up Time

10mS min. @ 120VAC and max. load

Short Circuit Protection

>120%, auto restart

Over Voltage Protection

>120%, Zener Clamp

ENVIRONMENTAL:

Temperature

Operation 0 to +50°C

Non-operation -20 to +75°C

Humidity

Operation 0 to 90%

Emissions

FCC Class B

EN55022 Class B

Dielectric Withstand (Hi-pot) Test

Primary to Secondary: 3000VAC

DC Output Connector

Micro-USB

AC Input Clips (sold separately)

US: RPA

Europe: RPE

UK: RPK

Australia: RPS

China:RPC

Argentina:RPN

